

MATERIAL SAFETY DATA SHEET

Page 1 of 2
Issued 01/02/2007

PRODUCT: **SEALIT MEMBRANE DAMPCOURSE**

Not classified as hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

Company Details	SHALEX PTY LTD (ABN 44125894224)
Address	P O Box 660 Arundel DC QLD 4214
Telephone/Fax	Tel (07) 5529 0277 Fax (07) 5594 7677
Emergency Telephone	1300 720 535
Other Information	Note: Users should verify currency of this data sheet if more than 3 years old. The information contained in this material safety data sheet is believed to be accurate on the date of issue and in accordance with the information available to us. Persons dealing with products referred to in this material safety data sheet do so at their own risk. We accept no liability whatsoever for damage or injury however caused arising from use of this information or of suggestions contained herein.

IDENTIFICATION

Product Name	Sealit Membrane Dampcourse
Other Names	None Listed
Product Code	None Listed
UN No:	None allocated
Hazchem:	None allocated
D.G. Class:	None allocated
Pack. Grp.:	None allocated
Product Type:	Acrylic Waterproofing Compound
Major Ingredients:	Water based Acrylic- Emulsion
Poisons Schedule	Not scheduled
Product Use	Roll-on, Brush-on membrane

PHYSICAL PROPERTIES

Appearance:	White milky liquid
Odour:	Slight Acrylic/Ammonia
Viscosity:	Very High
pH:	8.0 - 9.0
Specific Gravity:	1.2 – 1.25
Flash Point:	Non Combustible
Solubility in Water:	Dilutable

OTHER PROPERTIES

Volatile Component	1900-2500ppm
Auto ignition Temp.	N/Avail
Stability	Stable

HEALTH HAZARD INFORMATION

Primary Routes of Exposure:

Inhalation:	Inhalation of vapour can cause headache, nausea, irritation of nose, throat & lungs.
Skin Contact:	Prolonged or repeated contact can cause skin irritation.
Eye Contact:	Direct contact can cause eye irritation.

FIRST AID INFORMATION

Inhalation:	Move subject to fresh air.
Skin Contact:	Wash affected areas thoroughly with soap & water. Consult a physician if irritation persists.
Eye Contact:	Flush eyes with large amount of water for at least 15 minutes, holding the eye lids apart. Consult a physician if irritation persists.
Ingestion:	If swallowed drink at least 2 glasses of water. Consult a physician.
Toxicity Data: (Typical)	Oral LD 50 (Rat): > 5000 mg/kg Dermal LD 50 (Rabbit): > 5000 mg/kg

PERSONAL PROTECTION

Wear protective clothing to minimise skin contact. Where splatter is likely, wear goggles.

FLAMMABILITY

Fire Hazards Material is non flammable

SAFE HANDLING INFORMATION

Storage	Store in a cool place and out of direct sunlight. Keep containers sealed when not in use. Store above 4°C and below 50°C.	
Transport	Road and Rail Transport (ACTDG): IATA Classification: Packaging Group NIL	Class NIL Class NIL

FIRE FIGHTING INFORMATION

Unusual Hazards: Dried film can burn.

Extinguishing Agents: Use extinguishing media appropriate for surrounding fire.

Storage Requirements: Store out of direct sunlight.

Spills & Clean Up: Contain spills with sand or earth. Remove to suitable container for disposal. Wash area and equipment with water. Do not allow cleaning water and/or runoffs to enter sewers, storm water or open bodies of water.

.....END OF MSDS.....

This MSDS has been developed according to Worksafe Australia / NOHSC guidelines.