

MATERIAL SAFETY DATA SHEET

Page 1 of 2
Issued 01/07/2009

PRODUCT: **SEALIT MULIT PURPOSE**

Not classified as hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

| | |
|----------------------------|--|
| Company Details | SHALEX PTY LTD (ABN 44125894224) |
| Address | P O Box 660 Arundel DC QLD 4214 |
| Telephone/Fax | Tel (07) 5529 0277 Fax (07) 5594 7677 |
| Emergency Telephone | 1300 720 535 |
| Other Information | Note: Users should verify currency of this data sheet if more than 3 years old. The information contained in this material safety data sheet is believed to be accurate on the date of issue and in accordance with the information available to us. Persons dealing with products referred to in this material safety data sheet do so at their own risk. We accept no liability whatsoever for damage or injury however caused arising from use of this information or of suggestions contained herein. |

IDENTIFICATION

| | |
|---------------------------|--|
| Product Name | Sealit Multi Purpose |
| Other Names | None Listed |
| Product Code | None Listed |
| UN No: | None allocated |
| Hazchem: | None allocated |
| D.G. Class: | None allocated |
| Pack. Grp.: | None allocated |
| Product Type: | Acrylic Waterproofing Compound |
| Major Ingredients: | Water based Acrylic- Emulsion |
| Poisons Schedule | Not scheduled |
| Product Use | Roll-on, Brush-on or spray-on membrane |

PHYSICAL PROPERTIES

| | |
|-----------------------------|------------------------|
| Appearance: | White milky liquid |
| Odour: | Slight Acrylic/Ammonia |
| Viscosity: | Low |
| pH: | 8.0 - 9.0 |
| Specific Gravity: | 1.05 – 1.15 |
| Flash Point: | Non Combustible |
| Solubility in Water: | Dilutable |

OTHER PROPERTIES

| | |
|----------------------------|-------------|
| Volatile Component | 900-1200ppm |
| Auto ignition Temp. | N/Avail |
| Stability | Stable |

HEALTH HAZARD INFORMATION

Primary Routes of Exposure:

| | |
|----------------------|--|
| Inhalation: | Inhalation of vapour can cause headache, nausea, irritation of nose, throat & lungs. |
| Skin Contact: | Prolonged or repeated contact can cause skin irritation. |
| Eye Contact: | Direct contact can cause eye irritation. |

FIRST AID INFORMATION

| | |
|-------------------------------------|---|
| Inhalation: | Move subject to fresh air. |
| Skin Contact: | Wash affected areas thoroughly with soap & water. Consult a physician if irritation persists. |
| Eye Contact: | Flush eyes with large amount of water for at least 15 minutes, holding the eye lids apart. Consult a physician if irritation persists. |
| Ingestion: | If swallowed drink at least 2 glasses of water. Consult a physician. |
| Toxicity Data: (Typical) | Oral LD 50 (Rat): > 5000 mg/kg Dermal LD 50 (Rabbit): > 5000 mg/kg |

PERSONAL PROTECTION

Wear protective clothing to minimise skin contact. Where splatter is likely, wear goggles.

FLAMMABILITY

Fire Hazards Material is non flammable

SAFE HANDLING INFORMATION

| | | |
|------------------|--|------------------------|
| Storage | Store in a cool place and out of direct sunlight. Keep containers sealed when not in use. Store above 4°C and below 50°C. | |
| Transport | Road and Rail Transport (ACTDG): IATA Classification: Packaging Group NIL | Class NIL Class NIL |

FIRE FIGHTING INFORMATION

Unusual Hazards: Dried film can burn.

Extinguishing Agents: Use extinguishing media appropriate for surrounding fire.

Storage Requirements: Store out of direct sunlight.

Spills & Clean Up: Contain spills with sand or earth. Remove to suitable container for disposal. Wash area and equipment with water. Do not allow cleaning water and/or runoffs to enter sewers, storm water or open bodies of water.

.....END OF MSDS.....

This MSDS has been developed according to Worksafe Australia / NOHSC guidelines.